



## Sat-Light Gold Series

# GL952XU X-Band Optical Link



## Features & Benefits

- Optimized for Professional Microwave Applications
- Wide Dynamic Range
- 15Km Transmission Distance
- Transmitter and Receiver Gain Control
- Front Panel Test Port
- Powerful Monitoring Features
- Compatible with all 1st Generation Sat-Light Products

## Product Description

Global Foxcom's Sat-Light X-Band fiber optic interfacility links transmit and receive uplink and downlink signals in the 7.25–8.4 GHz range between antennas and control rooms or NOCs. Global Foxcom's IFLs offer a high performance alternative to conventional coaxial-cabled systems, reducing the need for waveguide and minimizing signal attenuation.

The Sat-Light IFLs function as a transparent link, transmitting all satellite modulation formats carrying an entire polarization on each link.

System limitations in using coaxial cable are overcome by the simplicity and performance of fiber optic connections to provide the highest levels in signal quality. Global Foxcom achieves this by using state of the art lasers to provide high efficiency, low noise analog links.

A typical X-Band link consists of an optical transmitter that receives the RF signal, transmits it over a single mode fiber to an optical receiver and reconverts the optical signal to RF. Global Foxcom's advanced fiber optic technology reduces the attenuation, slope, phase shift, and group delay maintaining extremely low levels over distances of up to 15 kilometers.

The X-Band's link cost effective high performance lasers produce negligible chirp and optical distortion, which is critical for long distance links. The EAM monolithic design, versus connectorized component electro-optics, assures high performance along with excellent reliability. The links are provided with test ports, status and fault LEDs, and gain controls.

# Sat-Light Gold Series

## Specifications

### GL952XU X-Band Optical Link [7.25–8.4 GHz], 4dB Optical Budget

RF Specifications	Units	Typical	Minimum	Maximum
Frequency Range	GHz	7.25–8.4 GHz		
Link Gain	dB	Adjustable	0	0
Amplitude Response @ Unity Gain 7.25–8.4 GHz and 48 MHz	dB	±.70 ±.25		
Gain Stability @ Constant Temp	dB/24hr			±0.15
SFDR	dB/Hz		100	
CNR	dB		40	
Noise Figure (NF)	dB		22	
Output IP3 (OIP3)	dB		+15	
Third Order Inter-Modulation [IMD]	dBc	Adjustable	-55	-50
Group Delay Variation- linear 7.25–8.4 GHz	ns	0.5		
Optimal Input Signal Range – Total Power	dBm		-25	-5
RF Output Signal Range – Total Power	dBm		-25	-5
Maximum Input without damage for 60 sec	dBm			+5
Input/Output Impedance	Ohm	50		
TX/RX Input/Output VSWR @50 Ohm	dB		1.6:1	
RF Connector Type: Input/Output		SMA		
Test Port		SMA		
Test Port [front panel sample port]	dB	-20	-19	-21
Optical Specifications	Units	Typical	Minimum	Maximum
Optical Power Output	dBm		-3	0
Optical Budget / Distance 6 dB optical budget	dB/Km		15Km@1550nm	
Optical Connector Types		FC/APC		
Optical Wavelength	nm	1550/CWDM		
Electrical Specifications	Units	Typical	Minimum	Maximum
Supply Voltage	Vdc	13	12.7	18
Supply Current [TX] <sup>4</sup>	Amps	0.8		
Supply Current (RX)	Amps	0.5		
Physical Specifications	Units	Typical	Minimum	Maximum
Operating Temperature Range			-10	+55
Dimensions [D×W×H]		RX: 5" x 3" x 5" TX: 5" x 3" x 5"		

## Ordering Information

Model Number	Description
GL952XU-T	Gold X-Band Uplink Transmitter
GL952XU-R	Gold X-Band Uplink Receiver