



Sat-Light Gold Series

GL952KD Ku-Band Optical Downlink



Features & Benefits

- Optimized for Professional Satellite Applications
- Wide Dynamic Range
- 15Km Transmission Distance
- Transmitter and Receiver Gain Control
- Powerful Monitoring Features
- Compatible with all 1st Generation Sat-Light Products

Product Description

Global Foxcom's Sat-Light Ku-Band fiber optic interfacility links transmit and receive downlink signals in the 10.7-12.75 GHz range between antennas and control rooms or NOCs. Global Foxcom's IFLs offer a high performance alternative to conventional coaxial-cabled systems, reducing the need for waveguide and minimizing signal attenuation.

The Sat-Light IFLs function as a transparent link, transmitting all satellite modulation formats carrying an entire polarization on each link.

System limitations in using coaxial cable are overcome by the simplicity and performance of fiber optic connections to provide the highest levels in signal quality. Global Foxcom achieves this by using state of the art lasers to provide high efficiency, low noise analog links.

A typical Ku-Band link consists of an optical transmitter that receives the RF signal, transmits it over a single mode fiber to an optical receiver and reconverts the optical signal to RF. Global Foxcom's advanced fiber optic technology reduces the attenuation, slope, phase shift, and group delay maintaining extremely low levels over distances of up to 15 kilometers.

The Ku-Band's link cost effective high performance lasers produce negligible chirp and optical distortion, which is critical for long distance links. The EAM monolithic design, versus connectorized component electro-optics, assures high performance along with excellent reliability. The links are provided with status and fault LEDs, and gain controls.

Sat-Light Gold Series

Specifications

GL952KD Ku-Band Optical Downlink [10.7–12.75GHz], 3dB Optical Budget

RF Specifications	Units	Typical	Minimum	Maximum
Frequency Range	GHz	10.7-12.75		
Link Gain	dB	Adjustable	-10	+10
Amplitude Response @ Unity Gain 10.7-12.75GHz and 48 MHz	dB	±1 ±0.2		±2
Gain Stability @ Constant Temp	dB/24hr			±0.15
SFDR	dB/Hz		100	
CNR	dBc		50	
Noise Figure (NF)	dB			22
Output IP3 (OIP3)	dB		+20	
Third Order Inter-Modulation [IMD] ¹	dBc	Adjustable	-55	-50
Group Delay Variation- linear 10.7-12.75 GHz	ns	0.4		
Input Signal Range – Total Power	dBm		-5	-25
RF Output Signal Range – Total Power	dBm		-5	-25
Maximum RF Input without damage	dBm		+10	
Input/Output Impedance	ohm	50		
TX/RX Input/Output VSWR @50 Ohm	dB		1.4:1	
RF Connector Type Input/Output		SMA		
Optical Specifications	Units	Typical	Minimum	Maximum
Optical Power Output	dBm		-2	0
Optical Budget / Distance 3 dB optical budget	dB/Km		15Km@1550nm	
Optical Connector Types		FC-APC or LC-APC		
Optical Wavelength	nm	1550/CWDM		
Electrical Specifications	Units	Typical	Minimum	Maximum
Supply Voltage	Vdc	13	12.7	18
Supply Current [TX]	Amps	0.8		
Supply Current (RX)	Amps	0.5		
Physical Specifications	Units	Typical	Minimum	Maximum
Operating Temperature Range			-10	+55
Dimensions [D×W×H]		5" X 3" X 5"		

1. For two carriers at maximum input and output power

Ordering Information

Model Number	Description
GL952KD-T	T – Gold Ku-Band Downlink Transmitter
GL952KD-R	R – Gold Ku Band Downlink Receiver